

CIRRUS



SPECIFICATIONS:

DESCRIPTION

Wall-mounted ADA-compliant sconce featuring handcrafted glass diffuser is enclosed on top to conceal lamp if viewed from above.

LAMPING

Standard: 75W A19 120V incandescent, lamp not included. Dimmable with standard incandescent dimmer (not included). LED: 8W Replaceable LED source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 800 lumens, 30,000 hours, lamp included.

DIFFUSER

Diffuser shall be of glass in Opal Matte, Gold or Black decors.

CONSTRUCTION


Half circle shaped, stamped aluminum fitter (9" L x 4.625" H x 0.75" D) is powder coated white. Glass secured by stainless steel set screws.

MOUNTING

Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. Fixture is centered on the outlet box.

LABELS

UL or ETL Listed. Suitable for Wet Locations (interior or exterior use).



ORDERING:

FIXTURE	- LAMP OPTIONS
297107 Opal Matte	(blank) 1x 75W A19 Incan
2971BK Black	LED 1x 8W LED 120V,
2971GD Gold	dimmable

Ex. 297107 1 Lt. Cirrus Sconce w/ Opal Matte Glass, White Finish

Project Information:



CIRRUS SHOWN IN OPAL MATTE (297107)





2971BK



All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 1/22